

This section describes Office Ally's use of the interchange (ISA) and functional group (GS) control segments. Note that submissions to Office Ally are limited to one interchange (ISA) and one functional group (GS) per file. Files may contain up to 5000 transaction sets (ST).

## 837 INBOUND TRANSACTION

X12 Data	Description	Values Used	Comments
Element			
ISA01	Authorization	NA	NA
	Qualifier		
ISA02	Authorization Code	NA	NA
ISA03	Security Qualifier	NA	NA
ISA04	Security Information	NA	NA
ISA05	Sender Qualifier	30 or ZZ	30 or ZZ
ISA06	Sender Id	Trading Partner's Sender Id	Tax ID is preferred
ISA07	Receiver Qualifier	30 or ZZ	30 or ZZ
ISA08	Receiver Id	330897513	Office Ally Tax ID
ISA11 (4010)	Interchange Control	"U"	
	Standards ID		
ISA11 (5010)	Repetition Separator	"^" or your repetition separator	
ISA12	Interchange Control	00401 for 4010, 00501 for 5010	
	Version Num		
ISA15	Usage Indicator	Р	Production File
<u> </u>	Functional Id Code		For testing, send "OATEST" in the filename
GS01	Functional Id Code	Indicates transaction type	See HIPAA IG
GS02	Sender's Code	Trading Partner's Sender Code	No Suggestions
GS03	Receiver's Code	OA	Office Ally Business Units identified
			for translator routing purposes.
GS08	Version Release	Identifies the transaction in	See HIPAA IG
	Industry ID Code	ASC Terms	